

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

OR LIQUEFIED() PETROLEUM) AND (IC=F02D-041 OR IC=F01N-011
OR IC=F02D-037/02)

171 S1
75680 TIMING
22418 PILOT
S2 13 S1 AND (TIMING OR PILOT)
171 S1
75680 TIMING
22418 PILOT
28719 DIESEL
S3 28 S1 AND (TIMING OR PILOT OR DIESEL)
28 S3
2657707 PC=US (United States of America)
S4 14 S3 NOT PC=US

?t 4/5/2,4-11

4/5/2

DIALOG(R) File 351: Derwent WPI

(c) 2002 Thomson Derwent. All rts. reserv.

013880072

WPI Acc No: 2001-364284/200138

XRPX Acc No: N01-265917

Gas fuel internal combustion engine for vehicles, has controller for optimum fuel injections individually into interconnected main combustion chamber and ignition combustion chamber based on engine load

Patent Assignee: GH GOTO IKUEIKAI (GOTO-N)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 2001107809	A	20010417	JP 99284977	A	19991006	200138 B

Priority Applications (No Type Date): JP 99284977 A 19991006

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 2001107809	A		7	F02M-021/02	

Abstract (Basic): JP 2001107809 A

NOVELTY - The engine has main combustion chamber (8) in cavity (14) of piston and ignition combustion chamber (9) which are interconnected through passage (13). A controller is provided for optimum control of main and supplement fuel injection valves (11,12) which inject fuel individually into the chambers (8,9) based on engine load and ignition timing control of ignition plug (10) in chamber (9).

USE - For vehicles using natural gas as engine fuel.

ADVANTAGE - Improves fuel consumption economy by supplying fuel using supplement fuel injector only, as main and ignition combustion chambers are interconnected. Improves engine performance as optimum fuel injection control is performed based on engine load without need for a throttle valve.

DESCRIPTION OF DRAWING(S) - The figure shows schematic block diagram of gas fuel internal combustion engine. (Drawing includes non-English language text).

Main combustion chamber (8)

Ignition combustion chamber (9)

Ignition plug (10)

Fuel injection valves (11,12)

Passage (13)

Cavity (14)

pp: 7 DwgNo 1/6

Title Terms: GAS; FUEL; INTERNAL; COMBUST; ENGINE; VEHICLE; CONTROL;
OPTIMUM; FUEL; INJECTION; INDIVIDUAL; INTERCONNECT; MAIN; COMBUST;
CHAMBER; IGNITION; COMBUST; CHAMBER; BASED; ENGINE; LOAD
Derwent Class: Q52; Q53; Q54; X22